TECHNICAL SPECIFICATION

hushfree.XS HUS-AP-007

FOR BETTER PHONE CALLS, ONLINE MEETINGS AND PRIVATE CONVERSATIONS


HushFree.XS is an A-rated acoustic booth with new 500 lux lighting on the table top. The booth is designed for individual work, longer video conferences and phone calls. The booth is equipped with a fixed desk and hushAssistant. It offers the possibility to work in both standing and sitting positions (stool not included), allowing the user to adopt an optimal body position while working. The elegantly designed side LED face illumination ensures the user is even more visible during video calls.


DIMENSIONING

W/D/H: exterior 1060 x 900 x 2300 mm interior 842,5 x 805 x 2034 mm

Weight: 292 kg Weight with box: 361 kg

Logistic data is available on request.





ELECTRIC SYSTEM

POWER SUPPLY MODULE (basic): 1x power supply 230V.


 $\textbf{POWER SUPPLY MODULE} \ \ (\text{optional, as required}): \ \ \text{type A charger, 1x type C}$ charger with a total power 25W MAX.

POWER CABLE: black - access from the floor with 5000 mm overall length. Access from the booth exit, 3400 mm.

LAN PLUG CAT.6: available with 5000 mm total cable length, and available with 3400 mm at the booth exit.

MOTION SENSOR: located in the ceiling, activates lighting at 60% and ventilation systems at 100% of total power. Standby power consumption 5W.

Maximum power consumption of the product 0,12A - 28W.




LIGHTING

CEILING LIGHT: 2x LED 12W / 4000K / lux - 500 max. / lm 1000. LED SIDE LIGHT: 2x 2W.

VENTILATION SYSTEM

2 fans x 80 m³/h* / 31 seconds**





TECHNICAL SPECIFICATION

hushfree.XS HUS-AP-007



GLASS DOOR WITH LATCH HANDLE: acoustic, tempered and laminated safety glass 10 mm, 5.5.2 thickness, including the 5 mm glass, 2 mm acoustic sheet and 5 mm glass. Anti-collision marking - silkscreen integrated inside the 65 mm wide glass. Transparent glass.

REAR SIDE GLASS PANELS: acoustic and laminated glass 10 mm (RW= 34 dB), 5.5.2 thickness, including the 5 mm glass, 2 mm acoustic sheet and 5 mm glass. Placed in aluminum profiles with acoustic seal. Transparent glass. Matte version as an option.

DOOR HANDLE AND HINGES: painted in cosmos grey. Handle dimensions: 45 x 221 mm.

CASE: 3-layer honeycomb board with a thickness of 38 mm. Both sides covered with melamine and finished with ABS edging. Structure prepared for anti-seismic ground fixing.

HUSHDOOR.LIMITER: Door opening limiter. Mounted on the lower and upper hinge (2 pieces). After mounting, the acoustic cabin door opens to a maximum angle of 130 degrees. Made of black EPDM material with a hardness of 50° ShA.

4 integrated castors with levelling feet.



TABLE TOP: measuring 750 x 344 mm, with height 1049 mm. Made of 18 mm thick plywood covered with HPL laminate on both sides. Maximum load - 25 kg.

PANEL WITH CEILING LIGHT: in cosmos grey. Total dimensions 190 x 640 mm, hole prepared for smoke detector diameter 20 mm, hole prepared for sprinkler installation diameter 65 mm.

INTERIOR PANELS: Made as a composite based on PETFELT, polyester fleece and fabric. PUR fire-retardant foam with acoustic properties, re-bonded.

UPHOLSTERY Athlon Plus:

weight: 750 g/lm; composition: 56% polyester, 44% Trevira CS; flammability: cigarette (BS EN 1021-1), cigarettes and matches (BS EN 1021 1&2), CA TB 117-2013; light fastness: 5 (EN ISO 105BO2); pilling resistance: 5 (EN ISO 12945-2); abrasion resistance: 100.000 martindale cycles (EN ISO 12947-2); certification: OEKO-TEX® STANDARD 100.

INTEGRAL CARPETED FLOOR: complies with ASTM D2859 - 16 (2021), standard test method for ignitability characteristics of ready to use textile floor covering materials. Adapted to commercial intensive use (hotel room, hotel suite, boutique, shop, restaurant, conference room, high traffic office, reception, stairs). Graphite color.

HUSHASSISTANT: hushAssistant is a 4-inch (diameter 104 mm) round, highresolution touchscreen lighting and ventilation controller. Part of hushAssistant's functionality is to manage and display meeting room availability. The system can be integrated with the Microsoft 365 Business platform.

BOOTH OCCUPANCY INDICATOR (optional): booth occupancy light indicator, measuring $96 \times 96 \times 37$ mm, prepared to be integrated with the ventilation module power supply. Adapted to be positioned on the booth ceiling anywhere within 1000 mm of the fan housing. Actuated by a motion sensor.

ACOUSTIC RATING

Acoustic measurements according to ISO 23351-1:2020 - class A - D_{SA} 30,3 (dB).

SUSTAINABLE DEVELOPMENT

Hushoffice booths are manufactured in the ISO 9001 and 14001 certified production factory in Poland by Mikomax Smart Office. The production process complies with the ISO 14001 environmental management system standard. Hushoffice booths are packaged and delivered in lightweight, recyclable cardboard boxes.





















