TECHNICAL SPECIFICATION

hushmeet.L3 HUS-BX-012 + 1x HUS-BX-013

IMPORTANT MEETINGS DESERVE CONVENIENT SPACE

The perfect modular space for large formal meetings: host an important board meeting or large team meetings that may go a bit longer. Modules may be added to increase the size of the space.




DIMENSIONING




W/D/H: exterior 2600 x 2700 x 2300 mm interior 2382 x 2612 x 2018 mm

Weight: 957.5 kg Weight with crate: 1231.5 kg

Logistic data is available on request.









Ceiling light 41.4 W/4200 lm. 3000 K. Avg. [lux] 325. Min. [lux] 160. Max. [lux] 479.*

Calculation results of the LED light source on the tabletop inside the booth. The final amount of Lux depends on the lighting intensity in the office space

ELECTRIFICATION

LED ceiling light.


Power module: 2x power, 2x RJ45, 2x USB Type A 2.4A.

Motion sensor: activating lighting and airflow at 50% power. Located in the ceiling. Standby power consumption 0.3 W.

Power cable: access from ceiling or base (detailed information can be found in the Assembly Manual). 60 mm opening in the ceiling. White cable with threeprong grounded plug 230V. The total length of the cable - 4500 mm. The cable length for the exit of unit - 3600 mm.

RJ45 cable: the total length of the cable – 2400 mm. The cable length for the exit of unit - 1400 mm.

Maximum power consumption of the product 70 W.




4 Lighting and ventilation adjustment knobs 5 Power module



VENTILATION

12 fans. 52 m3/h* / 234 seconds**



* maximum performance of the single fan, taking into account losses in the ventilation system.
** total time of air change inside based on the volume and capacity of one fan.



TECHNICAL SPECIFICATION

hushmeet.L3 HUS-BX-012 + 1x HUS-BX-013



EXTERIOR

GLASS DOOR with LATCH HANDLE: acoustic, tempered and laminated safety glass 10 mm, 5.5.2 thickness including the thickness of 5 mm glass, 2 mm acoustic sheet and 5 mm glass. Clear color.

FRONT AND REAR SIDE GLASS PANELS: acoustic and laminated glass 10 mm (RW= 35 dB), 5.5.2 thickness including the thickness of 5 mm glass, 2 mm acoustic sheet and 5 mm glass. Placed in aluminum profiles with acoustic seal. Clear color. Frosted rear glass – optional.

The front glass panels and door are always equipped with anti-collision markings. Exact dimensioning is available on request.

PROFILES: for glass and door frame in cosmos grey color.

DOOR HANDLE AND HINGES: anodized aluminum or aluminum painted in cosmos grey color.

CASE: 3-layer honeycomb board with a thickness of 38 mm. Both sides covered with melamine and finished with ABS edging.

Removable base cover providing space for pallet jack access.



INTERIOR

TABLE (OPTIONAL): (W/D/H) 1200 x 1800 x 735 mm.

Tabletop supported by a metal leg 70 mm painted in cosmos grey color. Worktop made of 3-layer melamine chipboard, 25 mm thickness. Maximum load – $15\ kg$.

INTERIOR PANELS: high-density LDF (HDF) 3 mm thickness, covered with non-flammable polyurethane foam. Upholstered.

FLAME RETARDANT FOAM: complies with BS 5852: Part 2: 1982, Ignition source 5 (Crib 5).

UPHOLSTERY Wool:

weight: 325 g/m², composition: 70%WO, 20%PL, 5%PA, 5%AF, flammability: cigarette and match (BS-EN 1021-1, 2) (BS 5852-0, 1), CAL 117 (class 1), ASTM 84 (class 1), light fastness: 5 (EN ISO 105BO2), fastness to rubbing: wet: 4/5; dry: 4/5 (ISO 105-X12),abrasion resistance: 100.000 martindale cycles (EN ISO 12947-2).

UPHOLSTERY Petrus:

weight: 389 g/m², composition: 100%PL, abrasion resistance: 80.000 martindale cycles (EN ISO 12947-2), light fastness: 3-4 (EN ISO 105BO2).

UPHOLSTERY Haiti:

weight: 220 g/m^2 , composition: 100%PL, abrasion resistance: 100.000 martindale cycles (EN ISO 12947-2), pilling fastness: 5

INTEGRAL CARPETED FLOOR.

CARPET: complies with ASTM D2859 – 16 (2021), standard test method for ignitability characteristics of finished textile floor covering materials. Adapted to commercial intensive use (hotel room, hotel suite, boutique, shop, restaurant, conference room, high traffic office, reception, stairs). Graphite color.

SUSTAINABILITY

Hushoffice booths are manufactured in a ISO 9001 and 14001 certified production facility in Poland by Mikomax Smart Office. They are compliant with the ISO 14001 Environmental Management System Standard. Hushoffice is packed and delivered in light cardboard boxes which are recycle-friendly.



CERTIFICATION





* Made in EU





